

CLAIMS

1. A twisted pair cable comprising a plurality of pairs, each of said pairs comprising:  
two conductors, each of said conductors being covered with an inner layer insulator and an outer layer insulator, said conductors being eccentric with respect to the overall insulation of said inner and outer layer insulator.
2. A twisted pair cable comprising a plurality of pairs, each of said pairs comprising:  
two conductors, each of said conductors being covered with an inner layer insulator and an outer layer insulator, said conductors being separated by a distance S1 which is smaller than the separation S2 of conductors in adjacent pairs.
3. A twisted pair cable comprising a plurality of pairs, each of said pairs comprising two conductors, each of said conductors being covered with an inner layer insulator and an outer layer insulator defining an outer surface, said conductors being asymmetric such that said conductors are closer to each other than to conductors in adjacent pairs in contact at the outer surface opposite said conductors.
4. A twisted pair cable according to claim 1, wherein said conductors are closer to each other than to an outer surface opposite said conductors.
5. A twisted pair cable according to claim 4, wherein said inner insulator is an extrudable polymer, and wherein said outer insulator is an extrudable elastomer.
6. A twisted pair cable according to claim <sup>2</sup>5, wherein said extrudable polymer has a modulus of elasticity greater than 64 Kpsi at room temperature, a dielectric constant lower than 2.5 and a loss factor lower than 0.0003

SUB  
BI

5

10

15

20

25

30

3.6

SUB  
DISUB  
EI

f

5

9.8.

10

[illegible]

9.

4j0

20

5. 14

12  
14

6 1/2

30

10 i

A twisted pair cable according to claim 7, wherein said elastomer and said extrudable polymer are foamed.

13-16.

5

10

15

[illegible]

Add DB